

# Alfa Laval Indication units

## Sensing and control

### Introduction

The Alfa Laval Indication unit - Inductive is an electrical feedback unit that offers cost-effective operation and standard functionality for automated indication on the inductive side of Alfa Laval butterfly valves. Straightforward and easy to use, this indication unit provides information about valve operating status 24/7 while boosting productivity.

This inductive indication unit is compatible with any programmable logic controller (PLC) with a PNP/NPN interface.

### Application

The electrical indication unit is designed with inductive sensors for use with Alfa Laval butterfly valves in hygienic applications across the dairy, food, beverage, biotechnology, pharmaceutical and many other industries.

### Benefits

- Durable and cost-effective
- Precision operation
- Long service life
- Easy to operate

### Standard design


The Indication unit – inductive consists of steel and plastic components, seals, contact pins, and cable connection with socket, screw and cable gland. Easy to mount, this indication unit does not require any mechanical adjustments and must be installed between the air-operated actuator and the valve.

### Working principle

The Alfa Laval Indication unit – Inductive sensor is an inductive proximity switch that has non-contact electronic switching elements. It is activated by an electromagnet device known as a roller leaf. The standard output signal is always a digital signal (on/off) indicating the position of the valve.

### Certificates

CE



## TECHNICAL DATA

Communication	
Electrical design:	DC PNP
Operating voltage:	10...36 V DC
Output function:	2 x NO
Current consumption:	<15 mA
Current rating:	250 mA
Electrical connection:	M12 plug

## PHYSICAL DATA

Materials	
Steel parts:	Stainless steel
Plastic parts:	PBT; PC (polycarbonate)
Contact pins:	Gold-plated
Environment	
Working temperature:	-25 °C to +80 °C
Protection rating	IP 67



### Note!

Compatible brackets are available for the actuators and handles for LKB butterfly valves.  
The M12 counterpart (Socket) connector are not a part of the indication unit package. The wiring and pinout on the M12 plug has changed, compared to the previous indication units.

## Options

- Valve compatibility

## Accessories

- Various cable options

## Compatible actuators


LKLA ø85	Yes
LKLA ø133	Yes

## Compatible Valves

LKB	Yes
LKB-2	Yes

## Electrical connection

Standard M12 Connection	
Pin	Setup
1	Supply +
4	Closed: OUT + 1 (A1)
2	Open: OUT + 2 (A2)
3	Supply -



This document and its contents are subject to copyrights and other intellectual property rights owned by Alfa Laval AB (publ) or any of its affiliates (jointly "Alfa Laval"). No part of this document may be copied, re-produced or transmitted in any form or by any means, or for any purpose, without Alfa Laval's prior express written permission. Information and services provided in this document are made as a benefit and service to the user, and no representations or warranties are made about the accuracy or suitability of this information and these services for any purpose. All rights are reserved.

### How to contact Alfa Laval

Up-to-date Alfa Laval contact details for all countries are always available on our website at [www.alfalaval.com](http://www.alfalaval.com)